

## Option Board

## Applicable product

MODEL	Description	Application	R	Applicable product												
				MODEL	S	6	10		4	4	2		4	2	4	2
				DC-300	DC-330		DG-28	DG-38	DF-35		DP-85	DP-77	DP-75V	DP-65V		DC-101
AI-AD1	Analog Disc input	MM/MC Disc Equalyzer, A/D 20bit,fs48kHz	2	O	O		N	N	N		N	N	N	N		N
AI-U1	Line input / RCA	A/D 20bit,fs:48kHz	1	A	X		O	N	N		N	N	N	N		N
AI-B1	Line input / BAL	A/D 20bit,fs:48kHz	2	O	X		O	N	N		N	N	N	N		N
AI2-U1	Line input / RCA	A/D 24bit,fs:48/96kHz	1	B	A		B	O	O		N	N	N	N		N
AI2-B1	Line input / BAL	A/D 24bit,fs:48/96kHz	2	B	O		B	O	O		N	N	N	N		N
AIO-U1	Line In-Out / RCA	Only for Analog Tape Recorder 18bit A/D D/A	1	O	O		N	N	N		N	N	N	N		N
AIO-DGU1	Line In-Out for DG-28/(RCA)	Only for DG-28,applicable to play SA-CD	4	N	N		O	O	N		N	N	N	N		N
AIO-DGB1	Line In-Out for DG-28/(BAL)	Only for DG-28,applicable to play SA-CD	4	N	N		O	O	N		N	N	N	N		N
AO-U1	Line Output Boad (RCA)	4-MMB 20bit D/A Output 2.5V	1	O	O		N	N	N		N	N	N	N		N
AO-B1	Line Output Boad (BAL)	4-MMB 20bit D/A Output 2.5V	2	O	O		N	N	N		N	N	N	N		N
AO-U2	Line Output Boad (RCA)	4-MMB 20bit D/A Output 5.0V	1	N	N		O	C	N		N	N	N	N		N
AO-B2	Line Output Boad (BAL)	4-MMB 20bit D/A Output 5.0V	2	N	N		O	C	N		N	N	N	N		N
AO2-U1	Line Output Boad (RCA)	MDS plus 192kHz 24bit D/A Output 5.0V	1	N	N		O	O	N		N	N	N	N		N
AO2-B1	Line Output Boad (BAL)	MDS plus 192kHz 24bit D/A Output 5.0V	2	N	N		O	O	N		N	N	N	N		N
DI-ST1	HPC Optical Input	ST-Link Connection	1	X	X		N	N	X		X	X	X	X		X
DI-BNC1	HPC Coaxial input	BNC Connection	1	C	O		C	D	O		O	O	O	C		O
DI2-HS1	HS-Link Input	RJ-45 Connection	2	N	O		N	N	O		O	O	O	N		A
DIO-OC1	Opto/Coax In-Out	TOS-Link / RCA Connection	1	C	A		C	D	O		O	O	O	C		O
DIO-PRO1	AES/EBU In-Out	XLR Connection (AES/EBU)	2	O	O		O	E	O		O	O	O	O		O
DIO-ST1	HPC Optical In-Out	ST-Link Connection	1	C	O		C	D	O		O	O	O	C		O
DIO2-DG1	Only for DG-28 Broad Band In-Out	Put it to EXT DSP SLOT of Digital Equipment to play SA-CD	2	N	O		N	N	N		O	O	O	N		O
DO2-HS1	HS-Link Output	RJ-45 Connection	1	N	O		N	O	N		N	O	N	N		N

O : Applicable

X : Applicable,but not recommended

N : Not applicable

A : Standard

B : Applicable at fs:48kHz only

C : Applicable at fs:48kHz

D : Applicable at fs:96kHz

E : Applicable input fs:96kHz, output fs:48kHz

R : Required slot numbers

S : Solt numbers